

Accelerations, link, 102
 Active impedance, 211, 214, 218
 Actuator dynamics, 197
 Actuators, 167
 Adaptive control, 199
 Algebraic approach, 45
 Angular momentum, 82
 velocity vector, 54
 Arm mechanisms, 2
 Artificial constraints, 226
 Assignment of poles, 193
 Asymptotically stable, 168, 272
 atan2, 20, 259
 Avoiding obstacles, 249
 Avoiding singularities, 253

 Centrifugal force, 90
 Complementary sensitivity function, 189
 Compliance center, 214
 Compliance control, 222
 Computation, amount of, 175
 Computational load, 108
 Computed torque method, 174
 Condition number, 143
 Constraining force, 231
 Constraint frame, 224, 229
 Constraint surfaces, 228
 Control, 9
 dynamic hybrid, 227
 force, 211
 hybrid, 222
 of redundant manipulators, 244
 position, 155
 Controller, 9
 Control subsystem, 1
 Coordinate transformation, 23
 Coriolis force, 91
 Cosine theorem, 260
 Coupling inertia, 90
 Criterion function, 248
 Cylindrical-coordinate manipulators, 2, 139

 Damping coefficient, 184
 Decoupling control, 192
 Degrees of freedom, 2
 Denavit-Hartenberg notation, 33
 Desired trajectory, 155, 247
 Direct dynamics problem, 109
 Direct kinematics problem, 29, 39
 Direction cosine matrix, 17
 Disturbances, 172
 DME, 145
 Double-axis rotation method, 164
 Dual-sampling-rate approach, 176

Dynamic hybrid control, 227
 Dynamic manipulability, 143
 Dynamic-manipulability ellipsoid,
 Dynamic-manipulability measure,
 Dynamic parameters, 112
 Dynamics, 81

 Effective inertia, 90
 Elbow singularities, 70
 Elephant Trunk wrist, 4
 End effector, 39, 161, 227
 position of, 28
 velocity of, 57
 Equations of motion, 81
 Equivalent angle of rotation, 163
 Equivalent axis of rotation, 163
 ET wrists, 4
 Euclidean norm, 128, 247
 Euler angles, 18
 Euler method, 111
 Euler's equation, 82
 Evaluation of manipulators, 127

 Feedback compensator, 188
 Feedforward compensator, 188
 Fingers, 139
 Force, 71, 231
 Force control, 9, 211
 Force sensor, 11, 73, 120
 Force servo loop, 237
 Four-degrees-of-freedom wrist, 4
 Frame, 13
 Friction, 106, 121

 Gear ratio, 183
 Generalized coordinates, 86
 Generalized force, 87
 Geometric approach, 45
 Globally asymptotically stable, 273
 Gravity force, 91

 Hand, 14, 73, 139
 RCC, 212
 Homogeneous transform, 23
 Horizontal multi-joint type, 2
 Hybrid control, 222
 dynamic, 227

 IBM 7565 robotic system, 8
 Identifiable parameter, 115
 Identification, 112
 of load, 122
 Impedance control, 211
 Indices of manipulability, 142

Inertia matrix, 91
 Inertia tensor, 83, 93
 Inertial coordinate frame, 82
 Inertial force, 90
 Instantaneous axis of rotation, 54
 Instantaneous optimization problem, 249
 Integral action, 170
 Intermediate point, 158
 Inverse dynamics, 177
 Inverse dynamics problem, 108
 Inverse kinematics problem, 29, 45
 Inverse, of homogeneous transform, 26
 pseudo-, 67, 256, 263

 Jacobian matrix, 53, 57, 63, 246
 Joint actuators, 9
 Joint angle, 33
 Joint axis, 33
 Joint length, 33
 Joint variable, 28
 Joint-variable scheme, 155
 Joint vector, 28
 Joint velocity, 57

 Kawasaki Unimate, 8
 Kinematic equation, 29, 47, 51
 Kinematic parameters, 112
 Kinematics, 13
 Kinetic energy, 87

 Lagrange's equation, 86
 Lagrangian formulation, 81, 113
 Lagrangian function, 87
 Linear feedback control, 166
 Linearization, 170
 Linearizing compensation, 193
 Link accelerations, 102
 Link frames, 33
 Link length, 33
 Link parameters, 31
 Lyapunov function, 169, 203, 273
 Lyapunov stability theorem, 168
 Lyapunov stability theory, 202, 272

 Manipulability, 127
 dynamic, 143
 Manipulability ellipsoid, 128
 Manipulability measure, 131, 255
 Manipulating-force ellipsoid, 133
 Manipulation vector, 246
 Manipulators, 1
 Mechanisms, 1
 Modeling error, 172
 Moment, 72

Moments of inertia, 84
 Momentum, 82
 Motion subsystem, 1

 Natural angular frequency, 184
 Natural constraints, 226
 Negative definite, 275
 Newton's equation, 82
 Newton-Euler formulation, 81, 100
 Normalization, 131, 146
 Nyquist stability criterion, 189

 Object frame, 13
 Obstacle, 249
 Open-loop link mechanisms, 1
 Optimal configurations, 133
 Orientation of objects, 13
 Orthogonal-coordinate manipulators, 2,
 139

 Parallel-axis theorem, 94
 Parallel drive, 98, 125
 Parallel processing, 176
 Parallelogram, 125
 Parameter estimation, 202
 Passive impedance, 211
 Perspective transform, 78
 PI control law, 224
 PID control law, 224
 Pieper's approach, 51
 Pivot joint, 1
 Point-to-point control, 168
 Polar-coordinate manipulators, 2, 139
 Polynomial, 156
 Position control, 9, 155
 of objects, 13
 servo loop, 237
 Positioning accuracy, 2
 Positive definite, 275
 Potential energy, 87
 Principal axes,
 of manipulability ellipsoid, 130
 of moment of inertia, 86
 Principal minors, 276
 Prismatic joint, 1, 63, 65
 Processor, 177
 Product of homogeneous transform, 26
 Products of inertia, 84
 Pseudo inertia matrix, 92
 Pseudo-inverse, 67, 256, 263
 PUMA, 6, 40, 52, 65, 70, 137

 RCC hand, 212
 Reachable region, 70

- Real time, 109
- Recognition subsystem, 1
- Reduction ratios, 167
- Redundant manipulators, 244
- Redundant representation, 17
- Reference frame, 13
- Regularization, 256
- Remote center compliance hand, 212
- Representational singularities, 56
- Resolved acceleration control, 174
- Revolute joint, 1, 63, 64
- Robot system, 1
- Robustness, 187
- Roll, pitch, and yaw angles, 22
- Rotation,
 - equivalent angle of, 163
 - equivalent axis of, 163
- Rotation matrix, 14
- Runge-Kutta method, 111
- Sampling period, 175
- SCARA, 9, 135
- Second-order system, 185
- Sensitivity, 187, 239
 - function, 189
- Sensors, 9, 11
- Serial drive, 91
- Servo compensation, 170
- Servo compensators, 182
- Servomechanism, 9
- Servomotor, 182
- Shoulder singularities, 70
- Simulation, 110
- Single-axis rotation method, 163
- Singular configuration, 4, 67, 131, 196, 253
- Singular-value decomposition, 129, 264, 268
- Singular values, 268
- Singularities, 70
 - representational, 56
- Skew coordinate system, 56
- Small gain theorem, 189
- Stability, 272
- Stability margin, 187, 239
- Stanford manipulator, 36
- Statics, 71
- Step response, 184
- Stiffness control, 222
- Stretching transform, 78
- Subtasks, 177, 245
- Sylvester's criterion, 276
- T3-786 robot, 7
- Task-decomposition approach, 245
- Third-order decoupled system, 198
- Third-order systems, 185
- Three Roll Wrist, 4
- Three-link manipulator, 46, 124, 249
- Trace, 91
- Tracking error, 201
- Trajectory control, 9
- Transform, 78
- Transmission ratio, 133
- Twist angle, 33
- Two-link manipulator, 30, 69, 88, 96, 98,
 - 117, 172, 235
- Two-link mechanism, 133, 148
- Two-stage control, 170, 200
- Universal joints, 4
- Vector product, 60
- Velocity, 53, 57, 60
- Vertical multi-joint type, 2
- Virtual work, 75
- Wrist, 4
- Wrist mechanisms, 2
- Wrist singularities, 70